

ELASTOCOL STICK



ACCESSORY PRODUCTS

APPLICATIONS

ROOFS

FOUNDATIONS

TECHNICAL DATA SHEET

ANZ-TDS-15-ELASTOCOL STICK

DESCRIPTION

ELASTOCOL STICK is a primer designed to enhance the adhesion of SOPREMA self-adhesive membranes on porous surfaces such as "DENS GLASS GOLD" and "DENS DECK" at temperatures above -10°C.

ELASTOCOL STICK is composed of SBS synthetic rubbers, adhesive enhancing resins and volatile solvents. It is also suitable to prime non-porous surfaces such as concrete, fibre cement, metal and wood.

METHOD OF APPLICATION

- ELASTOCOL STICK can be applied with a brush, a roll or a spray can. Shake well before using.
- It must be thoroughly dry before applying the waterproofing membrane. Drying time will vary depending on air and surface temperature and humidity.

WARNING: Do not accelerate drying of ELASTOCOL STICK by heating with a torch.

CLEANING

- Tools can be cleaned with petroleum solvents such as mineral spirits, varsol, xylene, etc.

FOR COMPLETE INFORMATION ON PRODUCT INSTALLATION, PLEASE CONSULT YOUR SOPREMA REPRESENTATIVE

PACKAGING

SPECIFICATIONS	ELASTOCOL STICK
Physical state	Liquid
Colour	Red
Coverage	Porous surfaces: 0.3 to 0.5 l/m ²
	Non-porous surfaces : 0.1 to 0.25 l/m ²
Packaging	19 l
Pail per pallet	36

PROPERTIES

PROPERTIES	ELASTOCOL STICK
Specific gravity at 20°C	0.79 kg/l
Solids by weight	24%
Brookfield Viscosity, 25 °C	200 cP
Drying time	15 to 60 minutes, depending on temperature and quantity applied.

(All values are nominal)



SOPREMA.COM.AU • +61 (3) 9221 6230

TDS_ELASTOCOL_STICK_11-2020

1/2

ELASTOCOL STICK



ACCESSORY
PRODUCTS

APPLICATIONS

ROOFS

FOUNDATIONS

TECHNICAL DATA SHEET

ANZ-TDS-15-ELASTOCOL STICK

STORAGE AND HANDLING

Shelf life: Up to 60 months in original sealed containers, in cool and ventilated area.
Store in a well ventilated area. Keep away from any source of heat, dampness, humidity, oxidising agents or direct sunlight.
Flammable before curing. Keep away from sources of ignition.

STATEMENT OF RESPONSIBILITY

The technical information and application advice given in this publication is based on the present state of our best knowledge. As the information herein is of a general nature, no assumption can be made as to a product's suitability for a particular use or application and no warranty as to its accuracy, reliability or completeness either expressed or implied is given other than those required by Commonwealth or State Legislation. The owner, their representative and/or the contractor are responsible for checking the suitability of products for their intended use.

Note: Field service where provided, does not constitute supervisory responsibility. Suggestions made by Soprema Australia Pty Ltd either verbally or in writing may be followed, modified or rejected by the owner, engineer or contractor since they are responsible for carrying out procedures appropriate to a specific application.



SOPREMA.COM.AU • +61 (3) 9221 6230

TTDS_ELASTOCOL_STICK_11-2020_RA

2/2