



ACCESSORY
PRODUCTS

APPLICATIONS

ROOFS

FLEXOCOL V

TECHNICAL DATA SHEET

ANZ-TDS-37-FLEXOCOL V

DESCRIPTION

FLEXOCOL V is a mono-component elastomeric and solvent based adhesive, liquid with low viscosity, resistant to water. FLEXOCOL V is used for bonding FLAGON PVC waterproofing membranes on vertical surfaces.

APPLICATION METHOD

- FLEXOCOL V can be spread and levelled using a squeegee, a roll, or a similar tool and applied on the whole surface of the membrane as well as the substrate
- After verifying the stickiness of the surface, install the FLAGON PVC membrane on the prepared substrate then apply a pressure on the membrane using a metal or rubber roll
- The setting of the adhesive is immediate while maximum adhesive level is obtained within few days

CLEANING

- The laying tools can be cleaned with acetone or Methyl Ethyl Ketone.

IMPORTANT NOTES

- Do not use FLEXOCOL V for bonding on polystyrene.
- Do not apply FLEXOCOL V on wet support.
- With a temperature below 10°C facilitate the evaporation of the solvent using hot air.

PACKAGING

SPECIFICATIONS	FLEXOCOL V
Physical state	Liquid
Coverage	500 g/m ²
Packaging	20 litres can
Pail per pallet	30

PROPERTIES

PROPERTIES	FLEXOCOL V
Specific weight at 25°C (g/cm ³)	1.18
Water solubility	Not insoluble
Consistency	Viscose liquid
Solvents	chloride hydrocarbons

STORAGE AND HANDLING

Shelf life: Up to 6 months in original sealed containers, in cool and ventilated area. Store in a dry and well-ventilated area at room temperature.

STATEMENT OF RESPONSIBILITY

The technical information and application advice given in this publication is based on the present state of our best knowledge. As the information herein is of a general nature, no assumption can be made as to a product's suitability for a particular use or application and no warranty as to its accuracy, reliability or completeness either expressed or implied is given other than those required by Commonwealth or State Legislation. The owner, their representative ans/or the contractor are responsible for checking the suitability of products for their intended use.



SOPREMA.COM.AU • +61 (3) 9221 6230

TDS_FLEXOCOL_V_11-2020_RA

1/1