RESISTO

ELASTOCOL STICK

PRIMER

A primer composed of SBS synthetic rubbers, resins and volatile solvents.

- Enhances the adhesion of self-adhesive membranes
- Easy and fast application
- Resistant to water, alcohol and most saline, alkaline and diluted acids solutions

PRODUCT PURPOSE

Application	Waterproofing complement	
Building Part	Roofing	Foundations
	Walls	
Substrates	Wood	Metal
	Concrete	

PRODUCT CHARACTERISTICS

Installation Method	Paint brush	Sprayer
	Roller	
Maximum exposure	Once dry, cover as soon as possible	

PACKAGING

Code	Containers	Indicative Covering	Quantity per Pallet
37446	18.9 l (5 US gal)	0.1 to 0.5 l /m^2 (0.02 to 0.1 US gal/10 ft^2) Depending on the surface porosity	36

PROPERTIES

Properties	ELASTOCOL STICK
Specific Gravity at 20 °C (68 °F)	0.79 kg/L (6.7 lb/gal US)
Color	Copper
Solids by Weight	24 %
Viscosity, Brookfield at 25 °C (77 °F)	200 cP

(All values are nominal)

RESISTO

ELASTOCOL STICK

INSTALLATION

Storage	Five years in its original closed packaging, in a cool, well-ventilated area. Store in a cool, dry place between 5 ° C and 40 ° C (41 ° C and 104 ° C).

Minimum Application Temperature	-10 °C (14 °F)

Tools Required		Paint brush		Sprayer
		Roller		

Surface Preparation	The substrate must be clean, dry and free of dust, grease or other contaminants.
Installation	1. Mix the product before and during application. 2. Apply the product according to the chosen method. 3. Allow the primer to dry before installing the waterproofing membrane. 4. The primer is dry when sticky to the touch, but not messy.
Drying time	Between 15 minutes and 1 hour, depending on ambient temperature and the applied amount.
Cleaning	Clean tools with petroleum solvents (mineral spirits, xylene, etc.).
Tricks / Tips	For greater efficiency, install the membrane or the sealing strip as soon as the primer is dry.

Recommendations/ Limitations	The membranes should be installed 4 hours after the application.
Warnings	Keep out of the reach of children. Properly close the container after each use. Keep out of the sun and away from ignition sources. During use, keep away from ignition sources. No smoking. After application, keep away from flames until solvent has evaporated. Harmful if swallowed, inhaled, or contacts the skin. Store in a closed room, well-ventilated by forced ventilation if necessary, and provide supervision from outside. Do not pour residues in drains.