

COLPLY ADHESIVE



ACCESSORY
PRODUCTS

APPLICATIONS

ROOFS

TECHNICAL DATA SHEET

ANZ-TDS-107-COLPLY ADHESIVE

DESCRIPTION

COLPLY ADHESIVE is a high quality, single component, asphalt cutback adhesive formulated specifically for adhering SBS-modified bitumen membrane systems.

COLPLY ADHESIVE is blended with specially selected and processed asphalt and performance additives with contribute to its smooth troweling consistency.

INSTALLATION PROCEDURE

SUBSTRATE:

Surfaces must be dry, clean and free of oil, grease, debris or dirt.

APPLICATION:

- COLPLY ADHESIVE is applied to approved, compatible substrates using 4.8 mm or 6.0 mm notched trowels.
- The application rate over approved absorptive or rough substrate surfaces vary, requiring.
- The minimum application temperature is 0 °C.
- Refer to the SOPREMA SBS Roofing Manual for additional application guidelines.

CLEANING:

Tools and uncured adhesive can be cleaned with solvents, such as mineral spirits, Varsol, Xylene, etc

FOR COMPLETE INFORMATION ON PRODUCT INSTALLATION, PLEASE CONSULT YOUR SOPREMA REPRESENTATIVE.

PACKAGING

Specifications	COLPLY ADHESIVE TROWEL GRADE
Colour	Black
Physical state	Liquid
Container	10 L 19 L
Coverage rate* Non-porous substrate	0.6 to 0.8 L/m ²
Coverage rate* Porous substrate	0.8 to 1.0 L/m ²

*Coverage rate may vary depending on the application technique and the substrate condition.
(All values are nominal)

PROPERTIES

PROPERTIES	STANDARDS	COLPLY ADHESIVE TROWEL GRADE
Density	-	0.90 kg/L
Solids by weight	-	75 %
Lap adhesion	ASTM D3019	3.5 kN/m
Fully cured	-	30 days*

*Curing time was determined under ideal application conditions [25 °C and 50% relative humidity] it will be longer at lower temperatures. Curing time will also varies on the quantity applied.



SOPREMA.COM.AU • +61 (3) 9221 6230

TDS_COLPLY_ADHESIVE_0522_RA

1/2

COLPLY ADHESIVE



ACCESSORY
PRODUCTS

APPLICATIONS

ROOFS

TECHNICAL DATA SHEET

ANZ-TDS-107-COLPLY ADHESIVE

STORAGE AND HANDLING

Storage: Up to 12 months in original sealed container, protected from moisture.

COLPLY ADHESIVE must be stored between 5 to 40 °C.

Store in a ventilated place, away from heat and direct sunlight.

STATEMENT OF RESPONSIBILITY

The technical information and applicatio advice given in this publication is based on the present state of our best knowledge. As the information herein is of a general nature, no assumption can be made as to a product's suitability for a particular use or application and no warranty as to its accuracy, reliability or completeness either expressed or implied is given other than those required by Commonwealth or State Legislation. The owner, their representative and/or the contractor are responsible for checking the suitability of products for their intended use.



SOPREMA.COM.AU • +61 (3) 9221 6230

TDS_COLPLY_ADHESIVE_0522_RA

2/2