

HPD UNIQUE IDENTIFIER: 26487

CLASSIFICATION: 07 27 00 Air Barriers

PRODUCT DESCRIPTION: SOPRASEAL STICK VP is a self-adhesive, sheet-applied, vapour permeable air barrier and weather-resistive barrier for exterior walls. This product can be used on most substrates, such as masonry, concrete, wood and gypsum. The air barrier assembly comprising SOPRASEAL STICK VP obtained the A1 classification when tested under CAN/ULC-S742.

Section 1: Summary

Nested Method / Material Threshold

CONTENT INVENTORY

Inventory Reporting Format <input checked="" type="radio"/> Nested Materials Method <input type="radio"/> Basic Method Threshold Disclosed Per <input checked="" type="radio"/> Material <input type="radio"/> Product	Threshold Level <input checked="" type="radio"/> 100 ppm <input type="radio"/> 1,000 ppm <input type="radio"/> Per GHS SDS <input type="radio"/> Other	Residuals/Impurities <input type="radio"/> Considered <input checked="" type="radio"/> Not Considered Explanation(s) provided for Residuals/Impurities? <input checked="" type="radio"/> Yes <input type="radio"/> No	<p><i>All Substances Above the Threshold Indicated Are:</i></p> Characterized <input type="radio"/> Yes Ex/SC <input checked="" type="radio"/> Yes <input type="radio"/> No <i>% weight and role provided for all substances.</i> Screened <input type="radio"/> Yes Ex/SC <input checked="" type="radio"/> Yes <input type="radio"/> No <i>All substances screened using Priority Hazard Lists with results disclosed.</i> Identified <input type="radio"/> Yes Ex/SC <input type="radio"/> Yes <input checked="" type="radio"/> No <i>One or more substances not disclosed by Name (Specific or Generic) and Identifier and/ or one or more Special Condition did not follow guidance.</i>
---	---	---	--

CONTENT IN DESCENDING ORDER OF QUANTITY

Summary of product contents and results from screening individual chemical substances against HPD Priority Hazard Lists and the GreenScreen for Safer Chemicals®. The HPD does not assess whether using or handling this product will expose individuals to its chemical substances or any health risk. Refer to Section 2 for further details.

- MATERIAL | SUBSTANCE | RESIDUAL OR IMPURITY**
GREENSCREEN SCORE | HAZARD TYPE
- POLYPROPYLENE BARRIER [POLYPROPYLENE LT-UNK] ACRYLIC ADHESIVE [UNDISCLOSED NoGS] SILICONIZED PET FILM [POLYETHYLENE TEREPHTHALATE (PET) LT-UNK] POLYDIMETHYLSILOXANE RUBBER (POLYSILICONE-11) NoGS]

Number of Greenscreen BM-4/BM3 contents ... 0
Contents highest concern GreenScreen Benchmark or List translator Score ... LT-UNK
Nanomaterial ... No

INVENTORY AND SCREENING NOTES:

No substance other than those listed in this HPD have been added to the finished product during its manufacturing. Residuals or impurities could not be considered because information was not provided to the manufacturer by the raw materials vendors. Ranges were given for various substances to protect proprietary information; .

VOLATILE ORGANIC COMPOUND (VOC) CONTENT

VOC Content data is not applicable for this product category.

CERTIFICATIONS AND COMPLIANCE See Section 3 for additional listings.

VOC emissions: CDPH Stantard Method - N/A

CONSISTENCY WITH OTHER PROGRAMS

Pre-checked for LEED v4 Material Ingredients Option 1 and Option 2

Third Party Verified?

- Yes
- No

PREPARER: Self-Prepared

VERIFIER:
VERIFICATION #:

SCREENING DATE: 2021-11-04

PUBLISHED DATE: 2021-11-04

EXPIRY DATE: 2024-11-04

Section 2: Content in Descending Order of Quantity

This section lists contents in a product based on specific threshold(s) and reports detailed health information including hazards. This HPD uses the inventory method indicated above, which is one of three possible methods:

- Basic Inventory method with Product-level threshold.
- Nested Material Inventory method with Product-level threshold
- Nested Material Inventory method with individual Material-level thresholds

Definitions and requirements for the three inventory methods and requirements for each data field can be found in the HPD Open Standard version 2.2, available on the HPDC website at: www.hpd-collaborative.org/hpd-2-2-standard

POLYPROPYLENE BARRIER

#: 47.0000 - 49.0000

MATERIAL THRESHOLD: 100 ppm

RESIDUALS AND IMPURITIES CONSIDERED: No

MATERIAL TYPE: Polymeric Material

RESIDUALS AND IMPURITIES NOTES: Residuals and impurities could not be considered as information was not available from raw material vendors.

OTHER MATERIAL NOTES: Top component of the product, responsible for its air barrier and water resistive performance, as well as its water vapour diffusion.

POLYPROPYLENE

ID: 9003-07-0

HAZARD SCREENING METHOD: Pharos Chemical and Materials Library

HAZARD SCREENING DATE: 2021-11-04 19:40:42

#: 100.0000 - 100.0000

GS: LT-UNK

RC: None

NANO: No

SUBSTANCE ROLE: Sealant

HAZARD TYPE

AGENCY AND LIST TITLES

WARNINGS

None found

No warnings found on HPD Priority Hazard Lists

SUBSTANCE NOTES: A vapour-permeable polypropylene membrane layer is encapsulated between two layers of non-woven polypropylene fabric.

ACRYLIC ADHESIVE

#: 40.0000 - 44.0000

MATERIAL THRESHOLD: 100 ppm

RESIDUALS AND IMPURITIES CONSIDERED: No

MATERIAL TYPE: Polymeric Material

RESIDUALS AND IMPURITIES NOTES: Residuals and impurities could not be considered as information was not available from raw material vendors.

OTHER MATERIAL NOTES: Central portion of the product, responsible for adhesion to various substrates.

UNDISCLOSED

ID: Undisclosed

HAZARD SCREENING METHOD: Pharos Chemical and Materials Library

HAZARD SCREENING DATE: 2021-11-04 19:40:42

#: 99.0000 - 100.0000

GS: NoGS

RC: None

NANO: No

SUBSTANCE ROLE: Adhesive

HAZARD TYPE

AGENCY AND LIST TITLES

WARNINGS

None found

No warnings found on HPD Priority Hazard Lists

SUBSTANCE NOTES: Vapour-permeable acrylic-based adhesive enables adhesion to various substrates while allowing water vapour diffusion. Exact composition of the acrylic polymer is not disclosed to protect proprietary information.

SILICONIZED PET FILM

#: 9.0000 - 11.0000

RESIDUALS AND IMPURITIES NOTES: Residuals and impurities could not be considered as information was not available from raw material vendors.

OTHER MATERIAL NOTES: Plastic film used on the back side of the product to protect adhesive. To be removed upon application, exposing adhesive and allowing SOPRASEAL STICK VP to be adhered onto a substrate.

POLYETHYLENE TEREPHTHALATE (PET)

ID: 25038-59-9

HAZARD SCREENING METHOD: **Pharos Chemical and Materials Library** HAZARD SCREENING DATE: **2021-11-04 19:40:43**

%: **97.0000 - 99.0000** GS: **LT-UNK** RC: **None** NANO: **No** SUBSTANCE ROLE: **Anti-adhesive agent**

HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS
None found		No warnings found on HPD Priority Hazard Lists

SUBSTANCE NOTES: The siliconized release film applied to the back of the product is composed primarily of PET polymer.

POLYDIMETHYLSILOXANE RUBBER (POLYSILICONE-11)

ID: 63394-02-5

HAZARD SCREENING METHOD: **Pharos Chemical and Materials Library** HAZARD SCREENING DATE: **2021-11-04 19:40:43**

%: **1.0000 - 3.0000** GS: **NoGS** RC: **None** NANO: **No** SUBSTANCE ROLE: **Anti-adhesive agent**

HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS
None found		No warnings found on HPD Priority Hazard Lists

SUBSTANCE NOTES: Substance responsible of the release property of the release film used on the back of the product.

Section 3: Certifications and Compliance

This section lists applicable certification and standards compliance information for VOC emissions and VOC content. Other types of health or environmental performance testing or certifications completed for the product may be provided.

VOC EMISSIONS

CDPH Standard Method - N/A

CERTIFYING PARTY: Self-declared

ISSUE DATE: 2020-06- EXPIRY DATE:

CERTIFIER OR LAB: N/A

APPLICABLE FACILITIES: N/A

23

CERTIFICATE URL:

CERTIFICATION AND COMPLIANCE NOTES: N/A - This product is an exterior product therefore is not to be tested for VOC emissions.

Section 4: Accessories

This section lists related products or materials that the manufacturer requires or recommends for installation (such as adhesives or fasteners), maintenance, cleaning, or operations. For information relating to the contents of these related products, refer to their applicable Health Product Declarations, if available.

SOPRASEAL VP PRIMER

HPD URL: No HPD available

CONDITION WHEN RECOMMENDED OR REQUIRED AND/OR OTHER NOTES:

The use of a primer may be required before the installation of SOPRASEAL STICK VP. In such cases, vapour-permeable SOPRASEAL VP PRIMER (27 g/L VOC content) must be used to maintain the full vapour diffusion potential of SOPRASEAL STICK VP.

Section 5: General Notes

Performance certification:

Classification A1 under CAN/ULC-S742

Third-party report dated 2015-08-29 by Exova

Maximum air leakage of assembly = 0.0150 L / s m² at 75 Pa

MANUFACTURER INFORMATION

MANUFACTURER: Soprema
ADDRESS: 1688 Jean-Berchmans-Michaud St.
 Drummondville QC J2C8E9, Canada
WEBSITE: www.soprema.ca

CONTACT NAME: Jean-François Côté
TITLE: Director, Standards and Scientific Affairs
PHONE: 819-478-8166 x.3290
EMAIL: jfcote@soprema.ca

The listed contact is responsible for the validity of this HPD and attests that it is accurate and complete to the best of his or her knowledge.

KEY

Hazard Types

AQU Aquatic toxicity	LAN Land toxicity	PHY Physical hazard (flammable or reactive)
CAN Cancer	MAM Mammalian/systemic/organ toxicity	REP Reproductive
DEV Developmental toxicity	MUL Multiple	RES Respiratory sensitization
END Endocrine activity	NEU Neurotoxicity	SKI Skin sensitization/irritation/corrosivity
EYE Eye irritation/corrosivity	NF Not found on Priority Hazard Lists	UNK Unknown
GEN Gene mutation	OZO Ozone depletion	
GLO Global warming	PBT Persistent, bioaccumulative, and toxic	

GreenScreen (GS)

BM-4 Benchmark 4 (prefer-safer chemical)	LT-1 List Translator 1 (Likely Benchmark-1)
BM-3 Benchmark 3 (use but still opportunity for improvement)	LT-UNK List Translator Benchmark Unknown (the chemical is present on at least one GreenScreen Specified List, but the information contained within the list did not result in a clear mapping to a LT-1 or LTP1 score.)
BM-2 Benchmark 2 (use but search for safer substitutes)	
BM-1 Benchmark 1 (avoid - chemical of high concern)	
BM-U Benchmark Unspecified (due to insufficient data)	
LT-P1 List Translator Possible 1 (Possible Benchmark-1)	NoGS No GreenScreen.

Recycled Types

PreC Pre-consumer recycled content
PostC Post-consumer recycled content
UNK Inclusion of recycled content is unknown
None Does not include recycled content

Other Terms:

GHS SDS Globally Harmonized System of Classification and Labeling of Chemicals Safety Data Sheet

Inventory Methods:

Nested Method / Material Threshold Substances listed within each material per threshold indicated per material
Nested Method / Product Threshold Substances listed within each material per threshold indicated per product
Basic Method / Product Threshold Substances listed individually per threshold indicated per product

Nano Composed of nano scale particles or nanotechnology
Third Party Verified Verification by independent certifier approved by HPDC
Preparer Third party preparer, if not self-prepared by manufacturer
Applicable facilities Manufacturing sites to which testing applies

The Health Product Declaration (HPD) Open Standard provides for the disclosure of product contents and potential associated human and environmental health hazards. Hazard associations are based on the HPD Priority Hazard Lists, the GreenScreen List Translator™, and when available, full GreenScreen® assessments. The HPD Open Standard v2.1 is not:

- a method for the assessment of exposure or risk associated with product handling or use,
- a method for assessing potential health impacts of: (i) substances used or created during the manufacturing process or (ii) substances created after the product is delivered for end use.

Information about life cycle, exposure and/or risk assessments performed on the product may be reported by the manufacturer in appropriate Notes sections, and/or, where applicable, in the Certifications section.

The HPD Open Standard was created and is supported by the Health Product Declaration Collaborative (the HPD Collaborative), a customer-led organization composed of stakeholders throughout the building industry that is committed to the continuous improvement of building products through transparency, openness, and innovation throughout the product supply chain.

The product manufacturer and any applicable independent verifier are solely responsible for the accuracy of statements and claims made in this HPD and for compliance with the HPD standard noted.