



ACCESSORY
PRODUCTS

APPLICATIONS

ROOFS

FOUNDATIONS

CIVIL WORKS

SOPRADERE QUICK PRIMER

TECHNICAL DATA SHEET

ANZ-TDS-16-SOPRADERE QUICK PRIMER

DESCRIPTION

SOPRADERE QUICK is a ready-to-use cold applied fast drying bitumen emulsion primer composed of bitumen, volatile solvents and adhesive additives.

SOPRADERE QUICK is used as cold-applied primer on concrete, degreased metal or wood-based substrate, to increase the adhesion of SOPREMA bituminous waterproofing membranes hot bonded or torched-on.

INSTALLATION PROCEDURE

- SOPRADERE QUICK can be applied with a brush or roller on clean, dry substrates free of any residue that may hinder adherence. Shake well before using.
- It must be thoroughly dry before applying the waterproofing membrane. Drying time will vary depending on air and surface temperature and humidity.

WARNING: Do not accelerate drying of SOPRADERE QUICK by heating with a torch.

CLEANING

- Tools can be cleaned with petroleum solvents such as mineral spirits, varsol, xylene, etc.

RESTRICTION

- SOPRADERE QUICK is a highly flammable product.
- Store away from direct sunlight and open flame. Keep ignition sources away during application and until solvent has evaporated. Harmful if inhaled, swallowed or when in contact with the skin. In closed areas, ventilate carefully using mechanical means if necessary.
- Do not pour residues in drains.

PACKAGING

SPECIFICATIONS	SOPRADERE QUICK
Physical state	Liquid
Colour	Darck brown
Coverage	0.25 l/m ²
Packaging	5 to 25 l
Pails per pallet	36



SOPREMA.COM.AU • +61 (3) 9221 6230

TDS_SOPRADERE_QUICK_11-2023



ACCESSORY
PRODUCTS

APPLICATIONS

ROOFS

FOUNDATIONS

CIVIL WORKS

SOPRADERE QUICK PRIMER

TECHNICAL DATA SHEET

ANZ-TDS-61-SOPRADERE QUICK PRIMER

PROPERTIES

PROPERTIES	SOPRADERE QUICK
Dry content	> 40 % of weight
Density at 20°C	about 950 kg/m ³ (± 50)
Viscosity cup n°4 at 20°C	23 to 27 °C
Flash point, ASTM D56	+ 24°C
Drying time on smooth surfaces *	Less than 30 minutes

(All values are nominal)

* In all cases, drying time must allow complete evaporation of solvents.

FOR COMPLETE INFORMATION ON PRODUCT INSTALLATION, PLEASE CONSULT YOUR SOPREMA REPRESENTATIVE

STORAGE AND HANDLING

Shelf life: Up to 1 years in original sealed containers, in cool and ventilated area.

STATEMENT OF RESPONSIBILITY

The technical information and application advice given in this publication is based on the present state of our best knowledge. As the information herein is of a general nature, no assumption can be made as to a product's suitability for a particular use or application and no warranty as to its accuracy, reliability or completeness either expressed or implied is given other than those required by Commonwealth or State Legislation. The owner, their representative and/or the contractor are responsible for checking the suitability of products for their intended use.

Note: Field service where provided, does not constitute supervisory responsibility. Suggestions made by Soprema Australia Pty Ltd either verbally or in writing may be followed, modified or rejected by the owner, engineer or contractor since they are responsible for carrying out procedures appropriate to a specific application.



SOPREMA.COM.AU • +61 (3) 9221 6230

TDS_SOPRADERE_QUICK_11-2023_RA

2/2