



ACCESSORY
PRODUCTS

APPLICATIONS

WALLS

ROOFS

SOPRASEAL SEALANT S37S

TECHNICAL DATA SHEET

ANZ-TDS-110-SOPRASEAL SEALANT S37S

DESCRIPTION

SOPRASEAL SEALANT S37S is a low VOC, solvent-free, polyether adhesive-sealant. This fast-setting, moisture curing product is designed to be applied on most substrate without the need of primer.

SOPRASEAL SEALANT S37S provide strong and elastic bonds on most of construction materials as well as all SOPRASEAL membranes. SOPRASEAL SEALANT S37S can be applied at temperatures range from 10°C to 40°C with a pneumatic cartridge (no special tools or mixers required).

SOPRASEAL SEALANT S37S will not shrink upon curing or discolor when left exposed to UV. SOPRASEAL SEALANT S37S is fast setting and after 7 days is fully cured.

INSTALLATION PROCEDURE

APPLICATION:

- SOPRASEAL SEALANT S37S must be applied to clean, sound substrates
- SOPRASEAL SEALANT S37S tubes can be used with a standard cartridge extruder as an accessory sealant to all SOPRASEAL membranes.

FOR COMPLETE INFORMATION ON PRODUCT INSTALLATION, PLEASE CONSULT YOUR SOPREMA REPRESENTATIVE.

PACKAGING

| SPECIFICATIONS | SOPRASEAL SEALANT S37S |
|------------------|------------------------|
| Physical state | Viscous |
| Colour | Gray or White |
| Container | 600 mL |
| Units per Pallet | 1200 |

PROPERTIES

| PROPERTIES | SOPRASEAL SEALANT S37S |
|---------------------|------------------------|
| Surface drying time | 15-40min |
| Hardness Shore A | ≥ 40 |
| Tension strength | ≥ 2.0 MPa |
| Shear strength | ≥ 1.5 MPa |
| Elongation at break | ≥ 400% |
| Curing speed | 4.0 mm/d |

STORAGE AND HANDLING

Store unopened containers in a cool, dry area. Protect from water, heat and direct sunlight. Extreme temperatures will reduce shelf life. Temperature should be 10-25°C. Shelf life: 9 month

STATEMENT OF RESPONSIBILITY

The technical information and application advice given in this publication is based on the present state of our best knowledge. As the information herein is of a general nature, no assumption can be made as to a product's suitability for a particular use or application and no warranty as to its accuracy, reliability or completeness either expressed or implied is given other than those required by Commonwealth or State Legislation. The owner, their representative and/or the contractor are responsible for checking the suitability of products for their intended use.



SOPREMA.COM.AU • +61 (3) 9221 6230

TDS_SOPRASEAL_SEALANT_S37S_10-2023_V2_RA

1/1