

# Colphene LM 1100

## Safety Data Sheet

according to Hazardous Products Regulation (WHMIS Revision 7-8)  
according to Federal Register / Vol. 89, No. 98 / Monday, May 20, 2024 / Rules and Regulations (HAZCOM Revision 7-8)  
Issue date: 11/15/2018 Revision date: 9/10/2025 Supersedes: 11/15/2018 Version: 2.0

### **SECTION 1 Identification**

#### **1.1. GHS Product identifier**

Product form : Mixture  
Product name : Colphene LM 1100  
Document reference : CA U DRU SS FS 136

#### **1.2. Other means of identification**

No additional information available

#### **1.3. Recommended use of the chemical and restrictions on use**

Product usage : Roof restoration.

#### **1.4. Supplier's details**

Soprema Inc  
1640 rue Haggerty  
Drummondville, Québec J2C 5P8  
Canada  
T. + 1-877-626-6688

#### **1.5. Emergency phone number**

Emergency number : Chemtrec: + 1-800-424-9300 (Acct # CCN20515) (24h)  
Soprema: + 1-877-626-6688 (8h-17h Monday to Friday)

### **SECTION 2 Hazard identification**

#### **2.1. Classification of the substance or mixture**

##### **Classification (GHS CA)**

Flammable liquids, Category 3	H226	Flammable liquid and vapour
Germ cell mutagenicity, Category 1B	H340	May cause genetic defects.
Carcinogenicity, Category 1B	H350	May cause cancer.
Specific target organ toxicity, Repeated exposure, Category 1	H372	Causes damage to organs through prolonged or repeated exposure.
Hazardous to the aquatic environment, Chronic Hazard, Category 3	H412	Harmful to aquatic life with long lasting effects

Full text of H-statements: see section 16

#### **2.2. GHS label elements, including precautionary statements**

##### **GHS CA labelling**

Hazard pictograms :



Signal word : Danger

Hazard statements : H226 - Flammable liquid and vapour  
H340 - May cause genetic defects.  
H350 - May cause cancer.  
H372 - Causes damage to organs through prolonged or repeated exposure.  
H412 - Harmful to aquatic life with long lasting effects

# Colphene LM 1100

## Safety Data Sheet

according to Hazardous Products Regulation (WHMIS Revision 7-8)

according to Federal Register / Vol. 89, No. 98 / Monday, May 20, 2024 / Rules and Regulations (HAZCOM Revision 7-8)

Precautionary statements	: P201 - Obtain special instructions before use. P202 - Do not handle until all safety precautions have been read and understood. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P233 - Keep container tightly closed. P240 - Ground and bond container and receiving equipment. P241 - Use explosion-proof equipment. P242 - Use non-sparking tools. P243 - Take action to prevent static discharges. P260 - Do not breathe dust, fume, gas, mist, vapours, spray. P264 - Wash hands, forearms and face thoroughly after handling. P270 - Do not eat, drink or smoke when using this product. P273 - Avoid release to the environment. P280 - Wear protective gloves, protective clothing, eye protection, face protection, and hearing protection. P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water . P308+P313 - IF exposed or concerned: Get medical advice or attention. P314 - Get medical advice or attention if you feel unwell. P370+P378 - In case of fire: Use appropriate media to extinguish. P403+P235 - Store in a well-ventilated place. Keep cool. P405 - Store locked up. P501 - Dispose of contents and/or container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulations.
--------------------------	--

### 2.3. Other hazards which do not result in classification

No additional information available

## SECTION 3 Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	Conc. (% w/w)
Stoddard solvent, low boiling point naptha - unspecified	-	CAS-No.: 8052-41-3	10 – 25
Naphtha (petroleum), hydrotreated heavy; Low boiling point ydrogen treated naphtha	-	CAS-No.: 64742-48-9	10 – 25
Sulfur	-	CAS-No.: 7704-34-9	3 – 5

## SECTION 4 First-aid measures

### 4.1. Description of necessary first-aid measures

First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Rinse skin with water/shower. Take off immediately all contaminated clothing.
First-aid measures after eye contact	: Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.
First-aid measures general	: IF exposed or concerned: Get medical advice/attention.

# Colphene LM 1100

## Safety Data Sheet

according to Hazardous Products Regulation (WHMIS Revision 7-8)  
according to Federal Register / Vol. 89, No. 98 / Monday, May 20, 2024 / Rules and Regulations (HAZCOM Revision 7-8)

---

### 4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects after inhalation : None under normal conditions.  
Symptoms/effects after skin contact : None under normal conditions.  
Symptoms/effects after eye contact : None under normal conditions.  
Symptoms/effects after ingestion : None under normal conditions.

### 4.3. Indication of immediate medical attention and special treatment needed, if necessary

Other medical advice or treatment : Treat symptomatically.

## **SECTION 5 Fire-fighting measures**

### 5.1. Suitable extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.  
Unsuitable extinguishing media : Do not use a heavy water stream.

### 5.2. Specific hazards arising from the chemical

Fire hazard : Flammable liquid and vapour.  
Explosion hazard : No direct explosion hazard.  
Hazardous decomposition products in case of fire : Toxic fumes may be released.

### 5.3. Special protective actions for fire-fighters

Firefighting instructions : Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection.  
Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

## **SECTION 6 Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material damage.

Environmental precautions : Avoid release to the environment. Notify authorities if product enters sewers or public waters.

### 6.2. Methods and materials for containment and cleaning up

For containment : Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak without risks if possible.  
Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.  
Other information : Dispose of materials or solid residues at an authorized site.

For further information refer to section 13

# Colphene LM 1100

## Safety Data Sheet

according to Hazardous Products Regulation (WHMIS Revision 7-8)

according to Federal Register / Vol. 89, No. 98 / Monday, May 20, 2024 / Rules and Regulations (HAZCOM Revision 7-8)

### **SECTION 7 Handling and storage**

#### **7.1. Precautions for safe handling**

Precautions for safe handling	: Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Limit quantities of product at the minimum necessary for handling and limit the number of exposed workers. Provide local exhaust or general room ventilation. Floors, walls and other surfaces in the hazard area must be cleaned regularly. Do not breathe dust/fume/gas/mist/vapours/spray.
Hygiene measures	: Separate working clothes from town clothes. Launder separately. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.
Additional hazards when processed	: Not expected to present a significant hazard under anticipated conditions of normal use.

#### **7.2. Conditions for safe storage, including any incompatibilities**

Technical measures	: Ground/bond container and receiving equipment.
Storage conditions	: Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.
Packaging materials	: Store always product in container of same material as original container.

### **SECTION 8 Exposure controls/personal protection**

#### **8.1. Control parameters**

<b>Stoddard solvent, low boiling point naphtha - unspecified (8052-41-3)</b>	
<b>Canada (Alberta) - Occupational Exposure Limits</b>	
Local name	Stoddard solvent
OEL TWA	572 ppm 100 ppm
Regulatory reference	Alberta Regulation 191/2021
<b>Canada (Quebec) - Occupational Exposure Limits</b>	
Local name	Stoddard solvent (Petroleum distillates)
VEMP (OEL TWAEV)	525 mg/m <sup>3</sup> 100 ppm
Regulatory reference	S-2.1, r. 13 - Regulation respecting occupational health and safety
<b>Canada (British Columbia) - Occupational Exposure Limits</b>	
Local name	Stoddard solvent (mineral spirits)
OEL TWA	290 mg/m <sup>3</sup>
OEL STEL	50 mg/m <sup>3</sup>
Regulatory reference	OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC)
<b>Canada (Manitoba) - Occupational Exposure Limits</b>	
Local name	Stoddard solvent
OEL TWA	100 ppm

# Colphene LM 1100

## Safety Data Sheet

according to Hazardous Products Regulation (WHMIS Revision 7-8)

according to Federal Register / Vol. 89, No. 98 / Monday, May 20, 2024 / Rules and Regulations (HAZCOM Revision 7-8)

<b>Stoddard solvent, low boiling point naphtha - unspecified (8052-41-3)</b>	
Notations and remarks	TLV® Basis: Eye, skin, & kidney dam; nausea; CNS impair
Regulatory reference	ACGIH 2024
<b>Canada (New Brunswick) - Occupational Exposure Limits</b>	
Local name	Stoddard solvent
OEL TWA	100 ppm
Notations and remarks	Eye, skin, & kidney dam;
<b>Canada (Newfoundland and Labrador) - Occupational Exposure Limits</b>	
Local name	Stoddard solvent
OEL TWA	100 ppm
Notations and remarks	TLV® Basis: Eye, skin, & kidney dam; nausea; CNS impair
Regulatory reference	ACGIH 2024
<b>Canada (Nova Scotia) - Occupational Exposure Limits</b>	
Local name	Stoddard solvent
OEL TWA	100 ppm
Notations and remarks	TLV® Basis: Eye, skin, & kidney dam; nausea; CNS impair
Regulatory reference	ACGIH 2024
<b>Canada (Nunavut) - Occupational Exposure Limits</b>	
Local name	Stoddard solvent
OEL TWA	100 ppm
OEL STEL	125 ppm
Regulatory reference	Occupational Health and Safety Regulations, Nu Reg 003-2016 (Amendment R-044-2021)
<b>Canada (Northwest Territories) - Occupational Exposure Limits</b>	
Local name	Stoddard solvent
OEL TWA	100 ppm
OEL STEL	125 ppm
Regulatory reference	Occupation Health and Safety Regulations R-039-2015 (R-013-2020)
<b>Canada (Ontario) - Occupational Exposure Limits</b>	
Local name	Stoddard solvent
OEL TWAEV	100 ppm
Regulatory reference	Ontario Occupational Exposure Limits under Regulation 833
<b>Canada (Prince Edward Island) - Occupational Exposure Limits</b>	
Local name	Stoddard solvent
OEL TWA	100 ppm
Notations and remarks	TLV® Basis: Eye, skin, & kidney dam; nausea; CNS impair
Regulatory reference	ACGIH 2024

# Colphene LM 1100

## Safety Data Sheet

according to Hazardous Products Regulation (WHMIS Revision 7-8)  
according to Federal Register / Vol. 89, No. 98 / Monday, May 20, 2024 / Rules and Regulations (HAZCOM Revision 7-8)

<b>Stoddard solvent, low boiling point naphtha - unspecified (8052-41-3)</b>	
<b>Canada (Saskatchewan) - Occupational Exposure Limits</b>	
Local name	Stoddard solvent
OEL TWA	100 ppm
OEL STEL	125 ppm
Regulatory reference	The Occupational Health and Safety Regulations, 2020. Chapter S-15.1 Reg 10
<b>Sulfur (7704-34-9)</b>	
<b>Canada (Alberta) - Occupational Exposure Limits</b>	
Local name	Sulphur
OEL TWA	10 mg/m <sup>3</sup>
Regulatory reference	Alberta Regulation 191/2021

### 8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.  
Environmental exposure controls : Avoid release to the environment.

### 8.3. Individual protection measures, such as personal protective equipment (PPE)

#### Personal protective equipment:

Wear recommended personal protective equipment.

<b>Hand protection:</b>
Protective gloves

<b>Eye protection:</b>
Safety glasses

<b>Skin and body protection:</b>
Wear suitable protective clothing

<b>Respiratory protection:</b>
[In case of inadequate ventilation] wear respiratory protection.

#### Personal protective equipment symbol(s):



## **SECTION 9 Physical and chemical properties**

### 9.1. Basic physical and chemical properties

Physical state : Liquid  
Appearance : Viscous liquid.  
Colour : Black

# Colphene LM 1100

## Safety Data Sheet

according to Hazardous Products Regulation (WHMIS Revision 7-8)  
according to Federal Register / Vol. 89, No. 98 / Monday, May 20, 2024 / Rules and Regulations (HAZCOM Revision 7-8)

Odour	: Solvent
pH	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: > 40 °C (Closed cup)
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapour pressure	: No data available
Relative vapour density at 20°C	: > 1 (Air=1)
Relative density	: 1.35
Solubility	: Insoluble in water.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: No data available
Explosive limits	: No data available
Particle characteristics	: No data available

### 9.2. Data relevant with regard to physical hazard classes (supplemental)

VOC content : 240 g/l

## **SECTION 10 Stability and reactivity**

Reactivity	: Flammable liquid and vapour.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No dangerous reactions known under normal conditions of use.
Conditions to avoid	: Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.
Incompatible materials	: No additional information available
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.
Hardening time:	: No additional information available

## **SECTION 11 Toxicological information**

### 11.1. Likely routes of exposure

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

<b>Sulfur (7704-34-9)</b>	
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 434 (Acute Dermal Toxicity - Fixed Dose Procedure)

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: May cause genetic defects.
Carcinogenicity	: May cause cancer.

<b>Sulfur (7704-34-9)</b>	
NOAEL (chronic, oral, animal/male, 2 years)	256 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)
NOAEL (chronic, oral, animal/female, 2 years)	284 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)

# Colphene LM 1100

## Safety Data Sheet

according to Hazardous Products Regulation (WHMIS Revision 7-8)

according to Federal Register / Vol. 89, No. 98 / Monday, May 20, 2024 / Rules and Regulations (HAZCOM Revision 7-8)

Reproductive toxicity : Not classified  
STOT-single exposure : Not classified  
STOT-repeated exposure : Causes damage to organs through prolonged or repeated exposure.

<b>Stoddard solvent, low boiling point naphtha - unspecified (8052-41-3)</b>	
STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard : Not classified  
Symptoms/effects after inhalation : None under normal conditions.  
Symptoms/effects after skin contact : None under normal conditions.  
Symptoms/effects after eye contact : None under normal conditions.  
Symptoms/effects after ingestion : None under normal conditions.

## **SECTION 12 Ecological information**

### **12.1. Toxicity**

Ecology - general : Harmful to aquatic life with long lasting effects.  
Hazardous to the aquatic environment, short-term (acute) : Not classified  
Hazardous to the aquatic environment, long-term (chronic) : Harmful to aquatic life with long lasting effects.

<b>Sulfur (7704-34-9)</b>	
LC50 - Fish [1]	866 mg/l Source: UBA, IUCLID
LC50 - Fish [2]	57.2 mg/l Test organisms (species): Prosopium williamsoni
EC50 - Crustacea [1]	≥ 5000 mg/l Source: ECOTOX
EC50 - Other aquatic organisms [1]	121.7 mg/l Test organisms (species): other:

### **12.2. Persistence and degradability**

<b>Stoddard solvent, low boiling point naphtha - unspecified (8052-41-3)</b>	
Persistence and degradability	Rapidly degradable

<b>Naphtha (petroleum), hydrotreated heavy; Low boiling point hydrogen treated naphtha (64742-48-9)</b>	
Persistence and degradability	Rapidly degradable

<b>Sulfur (7704-34-9)</b>	
Persistence and degradability	Rapidly degradable

### **12.3. Bioaccumulative potential**

<b>Sulfur (7704-34-9)</b>	
Partition coefficient n-octanol/water (Log Pow)	0.23

### **12.4. Mobility in soil**

No additional information available

### **12.5. Other adverse effects**

Ozone : Not classified  
Fluorinated greenhouse gases : No

# Colphene LM 1100

## Safety Data Sheet

according to Hazardous Products Regulation (WHMIS Revision 7-8)

according to Federal Register / Vol. 89, No. 98 / Monday, May 20, 2024 / Rules and Regulations (HAZCOM Revision 7-8)

---

### **SECTION 13 Disposal considerations**

Regional waste regulation	: Disposal must be done according to official regulations.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations	: Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	: Disposal must be done according to official regulations.
Additional information	: Flammable vapours may accumulate in the container. Do not re-use empty containers.

### **SECTION 14 Transport information**

In accordance with TDG / DOT / IMDG / IATA

#### **14.1. UN Number**

UN-No. (TDG)	: UN1999
UN-No. (DOT)	: UN1999
UN-No. (IMDG)	: 1999
UN-No. (IATA)	: 1999

#### **14.2. UN Proper Shipping Name**

Proper Shipping Name (TDG)	: TARS, LIQUID
Proper Shipping Name (DOT)	: Tars, liquid
Proper Shipping Name (IMDG)	: TARS, LIQUID
Proper Shipping Name (IATA)	: Tars, liquid

#### **14.3. Transport hazard class(es)**

##### **TDG**

Transport hazard class(es) (TDG)	: 3
Hazard labels (TDG)	: 3



##### **DOT**

Transport hazard class(es) (DOT)	: 3
Hazard labels (DOT)	: 3



##### **IMDG**

Transport hazard class(es) (IMDG)	: 3
Danger labels (IMDG)	: 3



##### **IATA**

Transport hazard class(es) (IATA)	: 3
Danger labels (IATA)	: 3

# Colphene LM 1100

## Safety Data Sheet

according to Hazardous Products Regulation (WHMIS Revision 7-8)  
according to Federal Register / Vol. 89, No. 98 / Monday, May 20, 2024 / Rules and Regulations (HAZCOM Revision 7-8)



### 14.4. Packing group, if applicable

Packing group (TDG) : III  
Packing group (DOT) : III  
Packing group (IMDG) : III  
Packing group (IATA) : III

### 14.5. Environmental hazards

Dangerous for the environment : No  
Other information : No supplementary information available.

### 14.6. Special precautions for user

**TDG**  
UN-No. (TDG) : UN1999  
Explosive Limit and Limited Quantity Index : 5 L  
Excepted quantities (TDG) : E1  
Passenger Carrying Road Vehicle or Passenger Carrying Railway Vehicle Index : 60 L  
Emergency Response Guide (ERG) Number : 130

**DOT**  
UN-No. (DOT) : UN1999  
DOT Special Provisions (49 CFR 172.102) : B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has a flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable.  
B13 - A nonspecification cargo tank motor vehicle authorized in 173.247 of this subchapter must be at least equivalent in design and in construction to a DOT 406 cargo tank or MC 306 cargo tank (if constructed before August 31, 1995), except as follows: a. Packagings equivalent to MC 306 cargo tanks are excepted from the certification, venting, and emergency flow requirements of the MC 306 specification. b. Packagings equivalent to DOT 406 cargo tanks are excepted from 178.3457(d)(5), circumferential reinforcements; 178.34510, pressure relief; 178.34511, outlets; 178.34514, marking, and 178.34515, certification. c. Packagings are excepted from the design stress limits at elevated temperatures, as described in Section VIII of the ASME Code (IBR, see 171.7 of this subchapter). However, the design stress limits may not exceed 25 percent of the stress for 0 temper at the maximum design temperature of the cargo tank, as specified in the Aluminum Association's Aluminum Standards and Data (IBR, see 171.7 of this subchapter).  
IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).  
T1 - 1.5 178.274(d)(2) Normal..... 178.275(d)(2)  
TP3 - The maximum degree of filling (in %) for solids transported above their melting points and for elevated temperature liquids shall be determined by the following: Degree of filling =  $95 * (dr / df)$  Where: df and dr are the mean densities of the liquid at the mean temperature of the liquid during filling and the maximum mean bulk temperature during transport respectively.

DOT Packaging Exceptions (49 CFR 173.xxx) : 150  
DOT Packaging Non Bulk (49 CFR 173.xxx) : 203  
DOT Packaging Bulk (49 CFR 173.xxx) : 242

# Colphene LM 1100

## Safety Data Sheet

according to Hazardous Products Regulation (WHMIS Revision 7-8)  
according to Federal Register / Vol. 89, No. 98 / Monday, May 20, 2024 / Rules and Regulations (HAZCOM Revision 7-8)

DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 60 L  
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 220 L  
DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.  
Reportable quantity (RQ) : 8000 lbs / 3632 kg (710.72 gal/ 2690.4 L) Package sizes shipped in quantities less than the product's declarable quantity are not subject to RQ (declarable quantity) transport requirements.

**IMDG**  
Special provisions (IMDG) : 955  
Limited quantities (IMDG) : 5 L  
Excepted quantities (IMDG) : E1  
Packing instructions (IMDG) : P001, LP01  
IBC packing instructions (IMDG) : IBC03  
Tank instructions (IMDG) : T1  
Tank special provisions (IMDG) : TP3  
EmS-No. (Fire) : F-E - FIRE SCHEDULE Echo - NON-WATER-REACTIVE FLAMMABLE LIQUIDS  
EmS-No. (Spillage) : S-E - SPILLAGE SCHEDULE Echo - FLAMMABLE LIQUIDS, FLOATING ON WATER  
Stowage category (IMDG) : A  
Properties and observations (IMDG) : Mobile liquids prepared by mixing asphalt with petroleum distillate. Pungent odour. Immiscible with water.

**IATA**  
PCA Excepted quantities (IATA) : E1  
PCA Limited quantities (IATA) : Y344  
PCA limited quantity max net quantity (IATA) : 10L  
PCA packing instructions (IATA) : 355  
PCA max net quantity (IATA) : 60L  
CAO packing instructions (IATA) : 366  
CAO max net quantity (IATA) : 220L  
Special provisions (IATA) : A3  
ERG code (IATA) : 3L

### 14.7. Transport in bulk according to Annex II of MARPOL 73/78<sup>9</sup> and the IBC Code<sup>10</sup>

Not applicable

## SECTION 15 Regulatory information

### 15.1. National regulations

**Stoddard solvent, low boiling point naphtha - unspecified (8052-41-3)**

Listed on the Canadian DSL (Domestic Substances List)

**Naphtha (petroleum), hydrotreated heavy; Low boiling point hydrogen treated naphtha (64742-48-9)**

Listed on the Canadian DSL (Domestic Substances List)

**Sulfur (7704-34-9)**

Listed on the Canadian DSL (Domestic Substances List)

# Colphene LM 1100

## Safety Data Sheet

according to Hazardous Products Regulation (WHMIS Revision 7-8)  
according to Federal Register / Vol. 89, No. 98 / Monday, May 20, 2024 / Rules and Regulations (HAZCOM Revision 7-8)

### Stoddard solvent, low boiling point naphtha - unspecified (8052-41-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active  
Listed on INSQ (Mexican National Inventory of Chemical Substances)

### Naphtha (petroleum), hydrotreated heavy; Low boiling point hydrogen treated naphtha (64742-48-9)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active  
Listed on INSQ (Mexican National Inventory of Chemical Substances)

### Sulfur (7704-34-9)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active  
Listed on INSQ (Mexican National Inventory of Chemical Substances)

## 15.2. International regulations

### UNITED STATES OF AMERICA

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

This product or mixture is not known to contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

## SECTION 16 Other Information

Issue date : 11/15/2018  
Revision date : 9/10/2025  
Supersedes : 11/15/2018

### Full text of hazard classes and H-statements:

H226	Flammable liquid and vapour
H340	May cause genetic defects.
H350	May cause cancer.
H372	Causes damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects

Safety Data Sheet (SDS), Canada- USA - Toxyscan 2025

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.