SOPRA-FOAM BIG GAP FILLER

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015) Issue date: 5/7/2024
Version: 1.0

SECTION 1: Identification

1.1. Product identifier

Product form	:	Mixture
Product name	:	SOPRA-FOAM BIG GAP FILLER
Product group	:	Trade product
Document reference	:	CA U DRU SS FS 354

1.2. Recommended use and restrictions on use

No additional information available

1.3. Supplier

Soprema Inc
1688 Jean-Berchmans-Michaud Street
Drummondville, Quebec J2C 5P8
Canada

1.4. Emergency telephone number

Emergency number	:	Canutec : +1-888-CANUTEC (226-8832) (North America) (24h) Chemtrec: +1-800-424-9300 (Acct # CCN20515 (24h) Soprema: +1-877-626-6688 (8h00 - 17h00)

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Classification (GHS CA/US)

Flammable aerosol Category 1	H222	Extremely flammable aerosol
Gases under pressure: Compressed gas	H280	Contains gas under pressure; may explode if heated
Skin corrosion/irritation Category 2	H315	Causes skin irritation
Serious eye damage/eye irritation Category 2	H319	Causes serious eye irritation
Respiratory sensitization, Category 1	H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin sensitization, Category 1	H317	May cause an allergic skin reaction
Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation	H335	May cause respiratory irritation
Specific target organ toxicity (repeated exposure) Category 2	H373	May cause damage to organs through prolonged or repeated exposure (Dermal, oral, Inhalation)

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS CA/US labeling

Hazard pictograms :

Signal word : Danger

Hazard statements :
H222 - Extremely flammable aerosol
H280 – Contains gas under pressure; may explode if heated.
H315 - Causes skin irritation
H317 - May cause an allergic skin reaction
H319 - Causes serious eye irritation
H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 - May cause respiratory irritation
H373 - May cause damage to organs through prolonged or repeated exposure (Dermal, oral, Inhalation)

Precautionary statements : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 - Do not spray on an open flame or other ignition source.
P251 - Do not pierce or burn, even after use.
P260 - Do not breathe mist, spray, vapors.
P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.
P264 - Wash thoroughly after handling.
P271 - Use only outdoors or in a well-ventilated area.
P272 - Contaminated work clothing should not be allowed out of the workplace.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P284 - [In case of inadequate ventilation] wear respiratory protection.
P302+P352 - IF ON SKIN: Wash with plenty of water.
P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312 - Call a POISON CENTER or doctor/physician if you feel unwell.
P314 - Get medical advice/attention if you feel unwell.
P321 - Specific treatment (see supplemental first aid instruction on this label).
P332+P313 - If skin irritation occurs: Get medical advice/attention.
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 - If eye irritation persists: Get medical advice/attention.
P342+P311 - If experiencing respiratory symptoms: Call a doctor, a POISON CENTER.
P362+P364 - Take off contaminated clothing and wash it before reuse.
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
P405 - Store locked up.
P410+P403 – Protect from sunlight. Store in a well-ventilated place.
P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
P501 - Dispose of contents / container by a local waste disposal company according to regional regulations.

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity

No additional information available

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	Conc. (% w/w)
Isocyanic acid polymethylenepolyphenylene ester ; Polymethylene polyphenylene isocyanate	Isocyanic acid polymethylenepolyphenylene ester ; Polymethylene polyphenylene isocyanate	CAS-No.: 9016-87-9	20 – 35
Isobutane	Isobutane	CAS-No.: 75-28-5	2.5 – 10
Dimethyl Ether	Dimethyl Ether	CAS-No.: 115-10-6	2.5 – 10

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor/physician if you feel unwell.

First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion : Call a poison center/doctor/physician if you feel unwell.

First-aid measures general : Call a poison center/doctor/physician if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation : May cause respiratory irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Symptoms/effects after skin contact : Irritation. May cause an allergic skin reaction.

Symptoms/effects after eye contact : Eye irritation.

Symptoms/effects after ingestion : None under normal conditions.

4.3. Immediate medical attention and special treatment, if necessary

Other medical advice or treatment : Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Unsuitable extinguishing media

Unsuitable extinguishing media : Do not use a heavy water stream.

5.3. Specific hazards arising from the hazardous product

Fire hazard : Extremely flammable aerosol.

Explosion hazard : No direct explosion hazard.

Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.4. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection.

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material-damage.

6.2. Methods and materials for containment and cleaning up

For containment : Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak, if possible without risk.

Methods for cleaning up : Mechanically recover the product.

Other information : Dispose of materials or solid residues at an authorized site.

6.3. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection"

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. Avoid contact with skin and eyes. Wear personal protective equipment.

Hygiene measures : Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

Additional hazards when processed : Not expected to present a significant hazard under anticipated conditions of normal use.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Keep in a cool, well-ventilated place away from heat.

Storage conditions : Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked up. Store in a well-ventilated place. Keep container tightly closed.

Incompatible products : No data available

Incompatible materials : No data available

Packaging materials : Store always product in container of same material as original container.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Isocyanic acid polymethylenepolyphenylene ester ; Polymethylene polyphenylene isocyanate (9016-87-9)	
Canada (Alberta) - Occupational Exposure Limits	
Local name	Polymethylene polyphenyl isocyanate (PAPI)
OEL TWA	0.07 mg/m³
	0.005 ppm
Regulatory reference	Alberta Regulation 191/2021

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Wear recommended personal protective equipment.

Hand protection:
Protective gloves

Eye protection:
Safety glasses

Skin and body protection:
Wear suitable protective clothing

Respiratory protection:
[In case of inadequate ventilation] wear respiratory protection.

Personal protective equipment symbol(s):

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	:	Liquid
Appearance	:	Aerosol.
Color	:	Yellow
Odor	:	characteristic
Odor threshold	:	No data available
pH	:	No data available
Relative evaporation rate (butyl acetate=1)	:	No data available
Relative evaporation rate (ether=1)	:	No data available
Melting point	:	Not applicable
Freezing point	:	No data available
Boiling point	:	No data available
Flash point	:	No data available
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
Flammability (solid, gas)	:	Extremely flammable aerosol
Vapor pressure	:	5 bar
Relative vapor density at 20°C	:	No data available
Relative density	:	No data available
Solubility	:	No data available
Partition coefficient n-octanol/water (Log Pow)	:	No data available
Viscosity, kinematic	:	No data available
Explosion limits	:	No data available

9.2. Other information

VOC content	:	< 2 g/l

SECTION 10: Stability and reactivity

Reactivity	:	Extremely flammable aerosol.
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reactions	:	No dangerous reactions known under normal conditions of use.
Conditions to avoid	:	Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.
Incompatible materials	:	No additional information available
Hazardous decomposition products	:	Under normal conditions of storage and use, hazardous decomposition products should not be produced.
Hardening time:	:	No additional information available

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	:	Not classified
Acute toxicity (dermal)	:	Not classified

Acute toxicity (inhalation) : Not classified

Isocyanic acid polymethylenepolyphenylene ester ; Polymethylene polyphenylene isocyanate (9016-87-9)	
LD50 oral rat	49000 mg/kg Source: Corporate Solution From Thomson Micromedex
LD50 dermal rabbit	> 9500 mg/kg Source: Corporate Solution From Thomson Micromedex
LC50 Inhalation - Rat (Vapours)	0.49 mg/l Source: Corporate Solution From Thomson Micromedex
ATE CA (oral)	49000 mg/kg body weight
ATE CA (vapors)	0.49 mg/l/4h

Skin corrosion/irritation : Causes skin irritation.

Serious eye damage/irritation : Causes serious eye irritation.

Respiratory or skin sensitization : May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction.

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Isocyanic acid polymethylenepolyphenylene ester ; Polymethylene polyphenylene isocyanate (9016-87-9)	
IARC group	3 - Not classifiable

Reproductive toxicity : Not classified

STOT-single exposure : May cause respiratory irritation.

Isocyanic acid polymethylenepolyphenylene ester ; Polymethylene polyphenylene isocyanate (9016-87-9)	
STOT-single exposure	May cause respiratory irritation.

STOT-repeated exposure : May cause damage to organs through prolonged or repeated exposure (Dermal, oral, Inhalation).

Isocyanic acid polymethylenepolyphenylene ester ; Polymethylene polyphenylene isocyanate (9016-87-9)	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard : Not classified

Sopra-Foam Big Gap Filler	
Vaporizer	Aerosol

Symptoms/effects after inhalation : May cause respiratory irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Symptoms/effects after skin contact : Irritation. May cause an allergic skin reaction.

Symptoms/effects after eye contact : Eye irritation.

Symptoms/effects after ingestion : None under normal conditions.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.

Hazardous to the aquatic environment, short–term (acute) : Not classified

Hazardous to the aquatic environment, long–term (chronic) : Not classified

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

Isocyanic acid polymethylenepolyphenylene ester ; Polymethylene polyphenylene isocyanate (9016-87-9)	
Partition coefficient n-octanol/water (Log Pow)	10.46 Source: Quantitative Structure Activity Relation

12.4. Mobility in soil

Isocyanic acid polymethylenepolyphenylene ester ; Polymethylene polyphenylene isocyanate (9016-87-9)

12.5. Other adverse effects

Ozone : Not classified

SECTION 13: Disposal considerations

13.1. Disposal methods

Regional waste regulation : Disposal must be done according to official regulations.
Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations : Disposal must be done according to official regulations.
Product/Packaging disposal recommendations : Disposal must be done according to official regulations.
Additional information : Do not re-use empty containers.

SECTION 14: Transport information

In accordance with TDG / DOT / IMDG / IATA

14.1. UN number

UN-No. (TDG) : UN1950
DOT NA No : UN1950
UN-No. (IMDG) : 1950
UN-No. (IATA) : 1950

14.2. UN proper shipping name

Proper Shipping Name (TDG) : AEROSOLS
Proper Shipping Name (DOT) : Aerosols, flammable, n.o.s.
Proper Shipping Name (IMDG) : AEROSOLS
Proper Shipping Name (IATA) : Aerosols, flammable

14.3. Transport hazard class(es)

TDG

Transport hazard class(es) (TDG) : 2.1
Hazard labels (TDG) : 2.1

DOT

Transport hazard class(es) (DOT) : 2.1
Hazard labels (DOT) : 2.1

IMDG

Transport hazard class(es) (IMDG) : 2.1

Hazard labels (IMDG) : 2.1

:

IATA

Transport hazard class(es) (IATA) : 2.1

Hazard labels (IATA) : 2.1

:

14.4. Packing group

Packing group (TDG) : Not applicable

Packing group (DOT) : Not applicable

Packing group (IMDG) : Not applicable

Packing group (IATA) : Not applicable

14.5. Environmental hazards

Other information : No supplementary information available.

14.6. Special precautions for user

TDG

UN-No. (TDG) : UN1950

TDG Special Provisions : 80 - Despite section 1.17 of Part 1 (Coming into Force, Repeal, Interpretation, General Provisions and Special Cases), a person must not offer for transport or transport these dangerous goods unless they are in a means of containment that is in compliance with the requirements for transporting gases in Part 5 (Means of Containment),107 - (1) These Regulations, except for Parts 1 and 2, do not apply to the offering for transport, handling or transport of UN1950, AEROSOLS, and UN2037, GAS CARTRIDGES, that contain dangerous goods included in Class 2.1 or Class 2.2 and that are transported on a road vehicle, a railway vehicle or a vessel on a domestic voyage, if the aerosols or gas cartridges have a capacity less than or equal to 50 mL.
(2) Subsection (1) does not apply to self-defence spray.

Explosive Limit and Limited Quantity Index : 1 L

Excepted quantities (TDG) : E0

Passenger Carrying Road Vehicle or Passenger Carrying Railway Vehicle Index : 75 L

DOT

UN-No.(DOT) : UN1950

DOT Special Provisions (49 CFR 172.102) : N82 - See 173.306 of this subchapter for classification criteria for flammable aerosols.

DOT Packaging Exceptions (49 CFR 173.xxx) : 306

DOT Packaging Non Bulk (49 CFR 173.xxx) : 304

DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : Forbidden

DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 150 kg

DOT Vessel Stowage Location : A - The material may be stowed ‘‘on deck’’ or ‘‘under deck’’ on a cargo vessel and on a passenger vessel.

DOT Vessel Stowage Other : 25 - Shade from radiant heat,87 - Stow ‘‘separated from’’ Class 1 (explosives) except Division 14,126 - Segregation same as for Class 9, miscellaneous hazardous materials

IMDG

Special provision (IMDG)	:	63, 190, 277, 327, 344, 381, 959
Limited quantities (IMDG)	:	SP277
Excepted quantities (IMDG)	:	E0
Packing instructions (IMDG)	:	P207, LP200
Packing provisions (IMDG)	:	PP87, L2
EmS-No. (Fire)	:	F-D - FIRE SCHEDULE Delta - FLAMMABLE GASES
EmS-No. (Spillage)	:	S-U - SPILLAGE SCHEDULE Uniform - GASES (FLAMMABLE, TOXIC OR CORROSIVE)
Stowage category (IMDG)	:	None
Stowage and handling (IMDG)	:	SW1, SW22
Segregation (IMDG)	:	SG69

IATA

PCA Excepted quantities (IATA)	:	E0
PCA Limited quantities (IATA)	:	Y203
PCA limited quantity max net quantity (IATA)	:	30kgG
PCA packing instructions (IATA)	:	203
PCA max net quantity (IATA)	:	75kg
CAO packing instructions (IATA)	:	203
CAO max net quantity (IATA)	:	150kg
Special provision (IATA)	:	A145, A167, A802
ERG code (IATA)	:	10L

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Canada regulations

Isocyanic acid polymethylenepolyphenylene ester ; Polymethylene polyphenylene isocyanate (9016-87-9)
Listed on the Canadian DSL (Domestic Substances List)

15.2. International regulations

UNITED STATES OF AMERICA

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.		
Isocyanic acid polymethylenepolyphenylene ester ; Polymethylene polyphenylene isocyanate	CAS-No. 9016-87-9	15 – 40%

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

Mexico regulations

Isocyanic acid polymethylenepolyphenylene ester ; Polymethylene polyphenylene isocyanate (9016-87-9)
Listed on INSQ (Mexican National Inventory of Chemical Substances)

SECTION 16: Other information

Issue date : 5/7/2024

Full text of H-phrases:	
H222	Extremely flammable aerosol
H280	Contains gas under pressure; may explode if heated
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation
H373	May cause damage to organs through prolonged or repeated exposure

Safety Data Sheet (SDS), Canada - USA - Toxyscan

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.